


Paint your own splash backs at a glance



BillieRalph

www.billieraph.com

PO Box 35243
Merivale
Christchurch

021339815

- Scratch resistant high gloss or matt surface finish
- Simply paint the rear with acrylic paint any colour you desire, the specially prepared paintable surface will not show brush marks with standard colour paints. Metal flake paints may show brush lines.
- The paint colour will not change, unlike on standard glass. This means you can use the same colour as your wall.
- Resene or Dulux test pots work perfectly [1 x Dulux, 2 - 3 Resene]
- PYO [Paint Your Own] splash back are available in 2 standard sizes 750 mm x 600 mm and 750 mm x 900 mm. Also available in custom sizes up to 3000 mm x 2000 mm
- PYO material is easily cut, planed, drilled etc for accurate fitting with standard tools. Fine tooth blades recommended.
- PYO splash back are suitable for use with electric or induction cook top. They are not suitable for use with gas, unless you have a 200 mm space from the flame, or an additional flame guard in place.
- PYO splash backs are also suitable for use in bathrooms, toilets and laundry areas etc. If used for waterproofing, please ensure an authorised waterproofing installer is used.
- 3 - 4 coats may be necessary to get a solid colour. If the wall behind the splash back is not even in colour, with some light colours, it may be best to apply a final coat of white or black to the rear of your splash back to avoid "colour transmission" through the splash back
- PYO splash backs are installed using 3M VHB adhesive tape. [supplied with the splash back]
- Allowance must be made for expansion and contraction with temperature changes. Generally this change is not from the cooking top use but direct sunshine on a dark painted surface, or general room heating variations.