

# Stone Veneer at a glance



BillieRalph

[www.billieralph.com](http://www.billieralph.com)

PO Box 35243  
Merivale  
Christchurch

021339815

- Slate Lite stone veneer come in 1200 x 610 x 2mm, 1200 x 2400 x 2 mm, 900 x 2240 x 2mm
- Ecotone comes in 1200 x 610 x 1mm
- Slate lite is suitable for interior and exterior use, general vertical or horizontal use. Floor use is limited to stone type and client wear expectation re marking etc
- Slate lite is installed like a tile with an adhesive applied with a 3 mm notched trowel.[holdfast wall and floor]
- Ecostone is for vertical application, installed with wall paper glue [specifically for cotton backed papers]
- Slate lite can be PVA bonded onto MDF, and machined traditionally. i.e. to make a counter top
- Slate lite can be cut with fine tooth woodworking blades, diamond blades are recommended for large amounts of cutting. A diamond blade in an angle grinder is recommended for simple on site cutting
- Ecotone is cut with a craft knife, from the back.
- both thicknesses should be sealed for protection and easy cleaning, specially suited sealers available
- Installation can be done in any pattern of your choice, with either dry joins or a decorative grout join
- Slate lite used on the exterior of a building is decorative only and is not a weather shield.
- Slate lite is suited to use around fires places [check re fire regulation], feature walls[interior or exterior], counter tops and even shower walls.
- Ecostone can be folded around a corner, application of heat to the rear will assist this. This make the installation appear like thick slabs of stone.
- For details re appropriate use, adhesive, cutting etc please contact [billieralph.com](http://billieralph.com)